



**EM-CRYL 600** modified acrylic latex admixture formulated to enhance performance by improving adhesion, flexibility, and curing properties when utilized with Pre-Krete products.

## TECHNICAL DATA

pH . . . . . 8 - 9  
Water Soluble . . . . . 100%  
Density . . . . . 8.7 lbs./gallon  
VOC . . . . . Compliant

EM-CRYL 600 modified mixes should not be applied when temperature is below 45°F or will fall below 45°F within 48 hours. Protect from freezing.

**COVERAGE:** When used as a bonding agent at full strength, 1 gallon will cover approximately 250-300 square feet over dense concrete or masonry.

**PACKAGING:** Gallons (4 per case), 5 Gallon Pails and 55 Gallon Drums

**COLOR:** Milky white, clear when dry

## APPLICATION

Refer to GUIDE SPECIFICATION – PRE-KRETE APPLICATION  
EM-CRYL 600 ACRYLIC ADDITIVE BONDING LIQUID METHODS

## CAUTION

Harmful if swallowed. If swallowed, induce vomiting and call physician immediately. May cause irritation to eyes and skin. Avoid contact. In case of skin contact wash affected area with soap and water. In case of eye contact, flush with water for 15 minutes and get prompt medical attention. The use of impervious rubber gloves and goggles is recommended when handling. Use with adequate ventilation and avoid breathing vapors and spray mist. Can cause irritation of the nose, throat and lungs. **Keep Out Of Reach Of Children.**

## MATERIAL SAFETY DATA SHEETS (MSDS)

Current MSDS are available on our website: [www.pre-krete.com](http://www.pre-krete.com)

## NOTES: